



PGD ARCH – User Instructions

Protection Group Denmark A/S

Messingvej 13

DK-8940 Randers SV

T: +45 60 54 25 83

contact@protectiongroup.dk

VAT No. 39592142

Installation of 10-Pad System

- Ensure the interior Velcro loop surface is clean.
- Install the large pad at the front of the helmet.
- Install the medium pad at the back of the helmet.
- Install four small pads in a line between the large and the medium pads.
- Distribute the four remaining small pads at the sides to your liking.

Installation of Velcro fields

- Clean and dry the helmet shell before installation.
- Remove backing and apply Velcro fields to the designated areas.
- Press firmly to ensure full adhesion.
- Velcro fields support helmet covers and cable routing.

Helmet Cover Installation

- Align the cover with the NVG shroud and side rails.
- Pull the cover over the shell and secure the Velcro straps to the Velcro coins on the inside on both the front and the back of the helmet shell.
- Ensure the cover does not obstruct rail or shroud interfaces.

Maintenance and Care

- Clean the shell and components using mild soap and water only.
- Do not use solvents, petroleum products or abrasive cleaners.
- Allow all components to air-dry completely before storage.
- Inspect screws, rails, shroud and straps regularly; tighten if required.
- Replace worn pads, straps or hardware with original PGD spare parts.
- Store the helmet in the provided bag when not in use.
- Remove the helmet from service after ballistic impact or visible structural damage.